

## SECTION 1 - IDENTIFICATION

**Product Identifier**

**Product Number(s)** #120069 - 6 oz.  
 #120014 - 1.5 oz.  
 #141002 - 6 oz. - Inactive Product  
 #101006 - 11oz. - Inactive Product  
 #150004 - 1.5 oz. - Inactive Product

**Product Name** Ballistol Multi-Purpose

**Other Means of Identification** None

**Relevant Identified Uses of the Substance or Mixture and Uses Advised Against**

**Identified Uses** Multi-purpose Lubricant

**Restrictions On Use** None identified

**24 hr Emergency  
Phone Number**

800-255-3924

(Chem-Tel – Contract #MIS001566)

Manufacturer Details		Supplier Details	
<b>Manufacturer Name</b>	Chem-Pak, Inc.	<b>Supplier Name</b>	Washington Trading Company, Inc. Ballistol USA
<b>Address</b>	242 Corning Way Martinsburg WV 25405	<b>Address</b>	One Cypress Knee Trail Kitty Hawk NC 27949
<b>Phone Number</b>	800-336-9828	<b>Phone Number</b>	252-261-6181
<b>Fax Number</b>	304-262-9643	<b>Fax Number</b>	252-261-0408

## SECTION 2 - HAZARDS IDENTIFICATION

**GHS/CLP (1272/2008) Classification of the Substance or Mixture**

HEALTH HAZARDS				PHYSICAL HAZARDS				
Acute Tox. Oral	Mutagenicity			Unstable Explosive	Refrigerated Liq. Gas		Pyrophoric Solid	
Acute Tox. Skin	Carcinogenicity			Explosive	Flammable Liquid		Emits Flammable Gas	
Acute Tox. Inhalation	Tox. to Reproduction			Flammable Gas	Flammable Solid		Oxidizing Liquid	
Skin Irritation	STOT SE			Aerosol	1	Self-Reactive Sub.	Oxidizing Solid	
Eye Irritation	STOT RE			Oxidizing Gas		Pyrophoric Liquid	Organic Peroxide	
Resp. Sensitization	Aspiration Hazard	1		Gas Under Pressure		Self-Heating Substance	Corrosive to Metal	
Skin Sensitization				<b>ENVIRONMENTAL HAZARDS</b>				
				Aquatic Acute		Aquatic Chronic	2	Ozone Depleting

**GHS/CLP (1272/2008) Label Elements**

**Hazard Pictograms**




**Signal Word**

*Danger!*

**Hazard Statements**

*Extremely flammable aerosol. Pressurized container: may burst if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.*

**NFPA / HMIS Classification**



HEALTH	*	1
FLAMMABILITY	4	
PHYSICAL HAZARD	0	

**Precautionary Statements**

**General**

**Prevention**

*Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.*

**Response**

*IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. Collect spillage.*

**Storage**

*Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122° F.*

**Disposal**

*Dispose of contents/container in accordance with local regulations.*

**Other Hazards Which Do Not Result In Classification**

**Hazards**

*None known*

**SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

ID	INGREDIENT	CAS NUMBER	EC NUMBER	INDEX NUMBER	% WT RANGE
1	White Mineral Oil	0008042-47-5	232-455-8	—	40 - 70
2	Liquefied Petroleum Gas	0068476-86-8	270-705-8	649-203-00-1	10 - 30
3	Iso-hexane	0000107-83-5	203-523-4	601-007-00-7	5 - 40

**SECTION 4 - FIRST-AID MEASURES**

**Description of First-Aid Measures**

**Eye Contact**

*Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.*

**Skin Contact**

*Remove with soap and water, rinsing and repeating for 15 minutes.*

**Ingestion**

*Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.*

**Inhalation**

*Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.*

**First-Aid Responder Protection**

*Wear adequate personal protective equipment based on the nature and severity of the emergency.*

**Most Important Symptoms and Effects, Both Acute and Delayed**

**Eye Contact**

*Liquid contact may cause pain along with moderate eye irritation.*

**Skin Contact**

*Adverse effects not anticipated.*

**Ingestion**

*Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.*

**Inhalation**

*Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.*

**Indication of Immediate Medical Attention and Special Treatment**

**Notes to Physician**

*Treat symptomatically.*

**Specific Treatments/Antidotes**

*Details on specific treatments and/or antidotes are not available.*

**Immediate Medical Attention**

*No information available.*

**SECTION 5 - FIRE-FIGHTING MEASURES**

### Suitable Extinguishing Media

**Extinguishing Media** Water, CO<sub>2</sub>, dry chemical, or universal aqueous film forming foam  
**Unsuitable Media** Water jet

### Specific Hazards Arising from the Chemical or Mixture

**Decomposition Products** Decomposition products may include oxides of carbon (CO, CO<sub>2</sub>), smoke, and/or vapors.  
**Hazards from the Product** Contents extremely flammable and under pressure. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to ignition an source.  
**Mechanical Impact Sensitivity** Mechanical impact may cause aerosol can to rupture, resulting in a rapid release of its contents. In the presence of an ignition source the liquid and/or vapor content may be ignited.  
**Static Discharge Sensitivity** Vapor within the flammable limits may be ignited by a static discharge of sufficient energy.

### Special Protection Actions for Fire-Fighters

**Protective Actions** Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.  
**Protective Equipment** Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**For Non-Emergency Personnel** No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.  
**For Emergency Responders** Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

### Environmental Precautions

**Precautions** Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

### Methods and Materials for Containment and Cleaning up

**Containment Procedures** Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents. DO NOT use combustible material such as sawdust.  
**Cleanup Procedures** Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.  
**Other Information** Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.  
**Prohibited Materials** Combustible absorbent material such as sawdust, use of equipment that may cause sparking.

## SECTION 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

**General Handling Precautions** KEEP OUT OF THE REACH OF CHILDREN. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.  
**Hygiene Recommendations** Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

### Conditions for Safe Storage Including And Incompatibilities

**Storage Requirements** Storage of individual cans should be done in an area below 55 °C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 3 Aerosol.

**Incompatibilities**

Segregate storage away from materials indicated in Section 10.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**Control Parameters**

**Occupational Exposure Limits**

ID	AUSTRALIA TWA	ALBERTA OEL	CANADA			GERMANY MAK	JAPAN OEL	MEXICO MPEL-PTA	UK WEL	OSHA PEL	UNITED STATES		
			BC TWA	ONTARIO TWA/EV	QUEBEC TWA						NIOSH REL	NIOSH IDLH	ACGIH TLV
1	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	–	3 mg/m <sup>3</sup>	–	–	–	–	–	–
2	1000 ppm	1000 ppm	1000 ppm	1000 ppm	–	–	–	–	1000 ppm	1000 ppm	2000 ppm	1000 ppm	1000 ppm

**Biological Exposure Indices**

ID	DETERMINANT	SAMPLING TIME	BEI	NOTATION
–	–	–	–	–

**Other Control Parameters**

Not available.

**Appropriate Engineering Control**

**Engineering Measures**

Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

**Individual Protection Measures**

**Hygiene Considerations**

Avoid breathing vapors and contact with the eyes. Always replace overcap when not in use. Keep out the reach of children.

**Thermal Hazards**

This product does not present a thermal hazard.

**Respiratory Protection**

An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.

**Skin Protection**

None normally required.

**Eye/Face Protection**

Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

**Other Protective Equipment**

Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Boiling Point</b>	> 51.7 °C (125.0 °F)	<b>Melting / Freezing Point</b>	Not Determined
<b>Flash Point, Liquid</b>	> -32.2 °C (-26.0 °F)	<b>Flash Point, Propellant</b>	-104.4 °C (-156.0 °F)
<b>Explosive Limits</b>	0.00% to 7.00%	<b>Autoignition Temperature, Liquid</b>	200.0 °C (392.0 °F)
<b>Flammability</b>	Extremely Flammable Aerosol	<b>Relative Density (H<sub>2</sub>O = 1)</b>	0.772 g/cc
<b>Molecular Weight</b>	Not Available	<b>Weight</b>	6.439 lbs/gal
<b>Vapor Pressure</b>	108 psig	<b>pH</b>	Not Available
<b>Vapor Density</b>	2.970 g/cc Maximum	<b>Evaporation Rate</b>	Not Available
<b>Form</b>	Pressurized Product	<b>Partition Coefficient</b>	Not Available
<b>Viscosity</b>	Not Available	<b>Refractive Index</b>	Not Available
<b>Odor Threshold</b>	Not Available	<b>Heat of Combustion</b>	Not Available
<b>Odor</b>	Characteristic	<b>Water Solubility</b>	Not Available
<b>Appearance / Color</b>	Clear to yellowish liquid	<b>Decomposition Temperature</b>	Not Available
<b>Percent Volatile</b>	25% Wt (34% Vol) Max	<b>VOC Content</b>	1.653 lbs/gal (197.995 g/L)
<b>Percent VOC</b>	25% Wt (34% Vol) Max	<b>HAP Content</b>	None
<b>Solids/Non Volatile Content</b>	75% Wt (66% Vol) Max	<b>Maximum Incremental Reactivity</b>	0.271 g O <sub>3</sub> /g



**Ecological Data**

ID	PERSISTENCE AND DEGRADABILITY				BIOACCUMULATIVE POTENTIAL		MOBILITY Koc
	PERSISTENCE	BOD	COD	ThOD	Pow / Kow	BCF	
-	-	-	-	-	-	-	-

**Other Adverse Effects** No additional information available.

**SECTION 13 - DISPOSAL CONSIDERATIONS**






**Waste Disposal** Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

**Waste Disposal of Packaging** In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

**Landfill Precautions** Not Available

**Incineration Precautions** \*\* DO NOT INCINERATE \*\* CONTENTS UNDER PRESSURE \*\*

**SECTION 14 - TRANSPORTATION INFORMATION**

	UNITED STATES DOT	INTERNATIONAL AIR ICAO/IATA	INTERNATIONAL OCEAN IMDG	UNITED NATIONS ADR	CANADA TDG
<b>ID Number</b>	UN1950	UN1950	UN1950	UN1950	UN1950
<b>Proper Shipping Name</b>	Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity	Aerosols, Limited Quantity	Aerosols, Limited Quantity
<b>Hazard Class(es)</b>	2.1	2.1	2.1	2.1	2.1
<b>Packing Group</b>	-	-	-	-	-
<b>Environmental Hazards</b>	No	No	No	No	No
<b>Special Precautions</b>	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
<b>Hazard Labels</b>					

**Additional Shipping Details** Not available.

**SECTION 15 - REGULATORY INFORMATION**

**United States - Federal Regulations**

ID	TSCA LISTED	SARA 302 EHS TPQ	RCRA	CERCLA	SARA 313	SARA 311/312			CLEAN AIR ACT		CLEAN WATER ACT
						FIRE	REACTIVITY	ACUTE	CHRONIC	HAP	
1	Yes	-	-	-	-	-	-	-	-	-	-
2	Yes	-	-	-	-	Yes	-	-	-	-	-
3	Yes	-	-	-	-	Yes	-	Yes	-	-	-

**United States - State Regulations**

ID	CA P-65	DE RQ	MA RTK CODES	ME TYPE RQ	RTK	MN AIR	WATER	NJ RTK	AIR	NY LAND	ACUTE	PA LISTED	WA PEL TWA	WI TABLE	WV TAP
3	-	-	6	-	-	-	-	-	-	-	-	Yes	-	-	-

**Canadian Regulations**

ID	WHMIS CATEGORIES										CHEMICAL LISTS		
	A	B	C	D1A	D1B	D2A	D2B	D3	E	F	DSL	NDSL	NPRI
1	-	-	-	-	-	-	-	-	-	-	Yes	-	-
2	X	B1	-	-	-	-	-	-	-	-	Yes	-	-
3	-	B2	-	-	-	-	-	-	-	-	Yes	-	-

**CPR Notice**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

**WHMIS Classification**

A, B5

**WHMIS Symbols**



**European Union Regulations**

ID	1907/2006 SVHC	1999/45/EC or 67/548/EEC CLASSIFICATION	HAZARD CODES	1272/2008 CLP PICTOGRAM CODES	SUPPL. CODES
2	-	F+	H220	GHS02, Dgr	-
3	-	F; Xn; N	H225, H304, H315, H336, H411	GHS02, GHS08, GHS07, GHS09, Dgr	-

**Classification According to EU Directive 1999/45/EC or 67/548/EEC (see Section 16 for full text)**

**Pictograms**



**Risk Phrases**

12-51/53-65-67

**Safety Phrases**

2-16-29-33-61-62

**International Regulations**

**Chemical Weapons Convention**

None of the ingredients are listed on the convention's schedules.

**SECTION 16 - OTHER INFORMATION**

**Full Text of EU Phrases and Precautionary Statements**

CODE	HAZARD STATEMENTS
H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

CODE	SUPPLEMENTAL HAZARDS
-	-

CODE	PRECAUTIONARY STATEMENTS
P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P251	Pressurized container: Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective eye protection/face protection.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C /122 °F.



# SAFETY DATA SHEET

GHS COMPLIANT

Ballistol Multi-Purpose

Part No. (See Section 1) Aerosol

Revision 6 / August 04, 2014

Page 8 of 9

CODE	RISK PHRASES
R 12	Extremely flammable.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65	Harmful: may cause lung damage if swallowed.
R 67	Vapours may cause drowsiness and dizziness.

CODE	SAFETY PHRASES
S 2	Keep out of reach of children.
S 16	Keep away from sources of ignition – No smoking.
S 29	Do not empty into drains.
S 33	Take precautionary measures against static discharges.
S 61	Avoid release to the environment. Refer to special instructions/Safety data sheets.
S 62	If swallowed do not induce vomiting: seek medical advice immediately and show this container or label.

#### SDS Revision History

Revision 1, 04/16/2002, Original  
Revision 2, 10/15/2004 New International Format, Updated information.  
Revision 3, 07/03/2013 Updated to GHS Version 4 Format  
Revision 4, 08/28/2013 Misc changes made at customer request.  
Revision 5, 02/12/2014 General updates.  
Revision 6, 08/04/2014 Updated formula for VOC Compliance, see Section 9.

#### Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

#### References and Sources

CAMEO Database of Hazardous Materials (<http://cameochemicals.noaa.gov>)  
CHEMpendium Database (<http://ccinfoweb.ccohs.ca/chempendium/search.html>)  
ChemSpider Chemical Database (<http://chemspider.com>)  
European Chemical Substances Information System (<http://esis.jrc.ec.europa.eu>)  
European Chemicals Agency (<http://echa.europa.eu>)  
International Chemical Safety Cards (<http://www.cdc.gov/niosh/ipcs/ipcscard.html>)  
IUCLID Chemical Data Sheets Information System (<http://esis.jrc.ec.europa.eu/index.php?PGM=dat>)  
Merck Chemical Database (<http://www.merckmillipore.co.uk/chemicals>)  
NIOSH Pocket Guide to Chemical Hazards (<http://www.cdc.gov/niosh/ngp/>)  
Right to Know Hazardous Substance Fact Sheets (<http://web.doh.state.nj.us/rtkhsfs/indexfs.aspx>)  
RTECS Database (<http://ccinfoweb.ccohs.ca/rtecs/search.html>)  
SOLV-DB, Solvent Database (<http://solvdb.ncms.org/solvdb.htm>)  
Toxic Substances Portal (<http://www.atsdr.cdc.gov/toxprofiles/index.asp>)  
TOXNet (<http://toxnet.nlm.nih.gov>)

#### Abbreviations Used

ACGIH	American Conference of Industrial Hygienists	LC50	Lethal Concentration 50%
ADR	European Agreement ... International Carriage of Dangerous Goods by Road	LD50	Lethal Dosage 50%
BCF	Bioconcentration Factor	MA	Massachusetts
BEI	Biological Exposure Index	MAK	Maximale Arbeitsplatz Konzentration (Maximum Workplace Concentration)
BOD	Biochemical Oxygen Demand	Max	Maximum
CA	California	mg/L	Milligrams per Litre
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act (USA)	mg/m <sup>3</sup>	Milligrams per Cubic Meter
CFR	Code of Federal Regulations (USA)	MN	Minnesota
CLP	Classification, Labeling and Packaging of Substances (Europe)	MPEL-PTA	Maximum Permissible Exposure Limit on Pondered Time Average
COD	Chemical Oxygen Demand	NDSL	Non-Domestic Substance List (Canada)
CPR	Controlled Products Regulations (Canada)	NIOSH	National Institute for Occupational Safety and Health (USA)
DE	Delaware	NJ	New Jersey
DOT	Department of Transportation (USA)	NOEC	No Observed Effect Concentration
DSL	Domestic Substance List (Canada)	NPRI	National Pollutant Release Inventory (Canada)
EC	European Community	NTP	National Toxicity Program (USA)
EC50	Effective Concentration 50%	NY	New York
EHA	Extremely Hazardous Substance	OEL	Occupational Exposure Limit
EPA	Environmental Protection Agency (USA)	OSHA	Occupational Safety and Health Administration (USA)
g/cc	Grams per Cubic Centimeter	P-65	Proposition 65 (USA)
GHS	Globally Harmonized System	PA	Pennsylvania
HAP	Hazardous Air Pollutant	Pow	Octanol-Water Partition Coefficient
IARC	International Agency for Research on Cancer	ppm	Parts per Million
IATA	International Air Transportation Association	psig	Pounds per Square Inch Gage
IC50	Half Maximal Inhibitory Concentration	RCRA	Resource Conservation and Recovery Act (USA)
ICAO	International Civil Aviation Organization	REL	Recommended Exposure Limit
IDLH	Immediately Dangerous to Life and Health	RQ	Reportable Quantity
IMDG	International Maritime Dangerous Goods	RTK	Right to Know
Kow	Octanol-Water Partition Coefficient	SARA	Superfund Amendments and Reauthorization Act (USA)
lbs/gal	Pounds per Gallon	SDS	Safety Data Sheet





# SAFETY DATA SHEET

GHS COMPLIANT

**Ballistol Multi-Purpose**

**Part No. (See Section 1) Aerosol**

Revision 6 / August 04, 2014

Page 9 of 9

SOCMI *Synthetic Organic Chemical Manufacturing Industry (USA)*  
STOT-RE *Suspected Target Organ Toxin, Repeat Exposure*  
STOT-SE *Suspected Target Organ Toxin, Single Exposure*  
SVHC *Substance of Very High Concern*  
TAP *Toxic Air Pollutant*  
TDG *Transportation of Dangerous Goods (Canada)*  
ThOD *Theoretical Oxygen Demand*  
TLV *Threshold Limit Value*  
TPQ *Threshold Planning Quantity*  
TSCA *Toxic Substances Control Act (USA)*  
TWA *Time Weighted Average*  
TWAEV *Time Weighted Average Exposure Value*  
VOC *Volatile Organic Compound*  
WA *Washington*  
WEL *Workplace Exposure Limit*  
WHMIS *Workplace Hazardous Materials Information System (Canada)*  
WI *Wisconsin*  
WV *West Virginia*